



## **Hypax Rusteze**

### Corrosion Preventive Liquid

#### **Product description**

Hypax Rusteze is specially formulated complete heavy-duty corrosion preventive for use on cast iron and steel, and non-ferrous metal items. It dries to leave a strong corrosion preventive film with excellent resistance to corrosion in harsh environments such as saline. Hypax Rusteze is used in applications requiring protection to MIL-PRF-16173E. The deposited film typically gives 3 years indoor protection or 12 months outdoor protection minimum.

#### **Typical analysis**

Property	Test	Units	Typical Analysis
Appearance	Visual		Brown paste/grease
Film type			Firm wax like
Solids content		% w/w	55-60
Density		Kg/l	0.85-0.95
Flash Point	ASTM D - 92	°C	41

#### **Application**

Hypax Rusteze can be applied by spraying or dipping to protect steel stored in area of high humidity, salt spray or acid fume environments. Typical use levels would be at 8 – 10 m<sup>2</sup> / litre dependant on thickness of film required. The addition of a additional hydrocarbon solvent and a small amount of butyl oitol (CAS. No. 111-76-2) can help dewatering properties for a thin film temporary protective. Films can easily be removed with a solvent based degreaser.

#### **Packaging**

Hypax Rusteze is available in 170 Kg steel drums and 900kg IBCs or as required by the customer.

The recommended shelf life of this product is 2 years.

Fulbeck Limited, Fulbeck Road, Newton Aycliffe. DL5 6TX. UK

Tel 0044 (0) 1325 314848. Fax 0044 (0) 1325 314969. [admin@fulbeck.uk.com](mailto:admin@fulbeck.uk.com)

This information is supplied in good faith to assist customers to assess the applicability of the material in their own products. No warranties are implied or given. ES18719