



Hypax Chain and Wire Rope Lubricant HD

Concentrated chain and wire rope lubricant

Product description

Hypax Chain and Wire Rope Lubricant HD is a concentrated product made of a complex mixture of anticorrosive materials, oils, lubricity agents and polybutene. It is designed to penetrate, lubricate and protect the surface of chains, gears and wire ropes to give excellent performance.

This product has anti-flick properties and so will remain on the surface of working parts for substantial periods of time and will protect and lubricate ferrous and non-ferrous metal surfaces.

Typical analysis

Property	Test	Units	Typical Analysis
Appearance	Visual		Greyish viscous liquid
Melting point	ASTM D127	°C	Liquid at room temperature
Viscosity @20°C	Brookfield		60000-90000 (after 24hrs)

Application

Hypax chain and wire rope lubricant HD can be diluted with oils or solvents to get the desired consistency for the specific use required, allowing it to be dip or brush coated onto the surface of the metal object.

Packaging

Wire rope lubricant is available in 170Kg steel drums and 900Kg IBCs or as required by the customer. The recommended shelf life of the product is 2 years.

Fulbeck Limited, Fulbeck Road, Newton Aycliffe, DL5 6TX, UK.

Tel +44 (0) 1325 314848. Fax +44 (0) 1325 314969. emma@fulbeck.uk.com

This information is supplied in good faith to assist customers to assess the applicability of the material in their own products.
No warranties are implied or given. ES060819