Hypax VCI oil

Anti-corrosive Oil with Volatile Corrosion Inhibitor

Product description

Hypax VCI Oil is an anti-corrosive liquid with the additional benefit of vapour phase protection. This means that in an enclosed space the vapour emitted by the product will protect metal surfaces from corrosion. The inhibitors used are ashless and, hence, if a small quantity is used in a fuel tank, removal is not essential since the product will simply dissolve in the fuel and burn away cleanly.

Typical analysis

Property	Test	Units	Typical Analysis
Appearance	Visual		Straw yellow liquid
Ph	5% in water		6.0-8.0
Flash point	ASTM D92	°C	>68
Specific gravity @20°C	Hydrometer	Kg/L	0.80-0.90
Viscosity @20°C	Flow cup	cSt	70-130

Application

Oil can be sprayed, applied by dip or with a brush. In an enclosed space it can be simply poured in before sealing. Use at 400 millilitres per cubic metre.

Packaging

Hypax VCI Oil is available in 25 litre, 205 litre and 1000 litre IBCs or as required by the customer.

Fulbeck Limited, Fulbeck Road, Newton Aycliffe, DL5 6TX, UK.
Tel. +44 (0) 1325 314848. Fax +44 (0) 1325 314969. emma@fulbeck.uk.com

This information is supplied in good faith to assist customers to assess the applicability of the material in their own products. No warranties are implied or given. ES231017